



# THERE'S A NEW WAY TO DO IT.

[www.active-srl.com](http://www.active-srl.com)

Olivator® - Our brand new olive harvester, designed for you.



# This is OLIVATOR®



## Handy and adaptable

Olivator® comes in four versions E1200, E4800, E5000, E5000BP which differ from each other in terms of capacity, engine and power supply. We are sure that your needs will be satisfied. To make our harvesters more versatile, each model is available in two sizes: L (Large) with telescopic rod extendable from 2100 to 3100 mm, and XL (Extra-Large), extendable from 2400 mm to 3700 mm.

## Innovative features

The four Olivator® versions have something in common: an innovation system that improves performance and ergonomics.

Each shaft group oscillate alternatively with wide moves. Together with 8 carbon shafts, this guarantees better productivity compared to traditional machines.

To facilitate the rod entry into the plant, the harvester head has been designed with a particular inclination that improves the teeth penetration into the branches.

All versions come with the engine fitted into the harvesting head, so that a transmission is not needed, thus reducing vibrations and improving the harvesting experience.



# That's why you need it

## Two parents

Olivator® product line has two mechanical patents. The first allows the two rake movement through a single connecting rod thus keeping the machine very light. The second patent covers the stabilization system which guarantee an improved harvesting performance.

## Weight

Olivator® is the lightest machines in its product category.

## No vibration

The special technical solutions we adopted, allow Olivator® harvesters to be vibration-free, considerably improving the operator's health and comfort!

## Performance

The alternative movement and wide oscillation of 8 carbon fiber rods, allows an extraordinary productivity.

## News 2021

Discover all the functionalities and features on our site!



# A model for each user

## Model L or XL

Available in two sizes, L or XL, each Olivator® model is perfect for every need. Exceptional ergonomics and weight balance help you work longer, always in a comfortable and safe way.

## With Battery

The E4800BP and E5000BP models include the ergonomic and lightweight backpack battery that allows incredible comfort even after several hours of work. The battery has been redesigned to be efficient and to help the brushless engine to operate smoothly.

# E-5000, E-5000 BP Models



## Olivator E-5000

Equipped with a cutting-edge brushless engine, it comes with an electronic board that manages the 3 operating speeds and working load. This olive harvester is the ideal solution for professional users looking for an advanced product, with high performance and long duration over time.

### Model L

**Lenght:** from 2100 to 3100 mm  
**Weight:** 2,5 kg  
**Productivity:** 90-120 Kg/h  
**Cable:** 20 mt with pliers  
**Power supply:** 12V/48V electric  
**Motor:** Brushless  
**Prong holder:** on a double bearing

### Model XL

**Lenght:** from 2400 to 3700 mm  
**Weight:** 2,8 kg  
**Productivity:** 90-120 Kg/h  
**Cable:** 20 mt with pliers  
**Power supply:** 12V/48V electric  
**Motor:** Brushless  
**Prong holder:** on a double bearing

## Olivator E-5000 BP

Our best performing olive harvester, designed for intensive use and equipped with next-gen lithium-ion backpack battery. Given its long-lasting duration (up to 7 hours), you'll be surprised by how light it is. And don't forget it comes with Olivator E-5000 iconic features: three working speeds, brushless motor and electronic management board.

**Lenght:** from 2100 to 3100 mm  
**Weight:** 2,5 kg  
**Productivity:** 90-120 Kg/h  
**Power supply:** Battery  
**Motor:** Brushless  
**Prong holder:** on a double bearing

**Lenght:** from 2400 to 3700 mm  
**Weight:** 2,8 kg  
**Productivity:** 90-120 Kg/h  
**Power supply:** Battery  
**Motor:** Brushless  
**Prong holder:** on a double bearing

## Dynamic indicators

The new ergonomic handle will allow you to check battery status whenever you want. The position of the cable has been specially designed to avoid accidental breakage and always ensure easy movements.



## Power is always under control!

Don't ever worry about running out of power, thanks to dynamic battery indicators.

**Autonomy:** 7 Hours  
**Weight:** 2.5 kg  
**Power supply:** 800W  
**Charging time:** 8 Hours



# E-1200 and 4800 Models

## OlivatorE-1200

This harvester has been specially designed for semi-professional users. The prongs-holder is fitted on a double bearing to ensure movement stabilization and a longer duration in time. The productivity is 80-110 kg/h, with only 2.5-2.8 kg of weight depending on the version.

### Model L

**Lenght:** from 2100 to 3100mm  
**Weight:** 2,5kg  
**Productivity:** 80/110 kg/h  
**Cable:** 10 mt with pliers  
**Power supply:** 12V electric  
**Motor:** with brushes

### Model XL

**Lenght:** from 2400 to 3700mm  
**Weight:** 2,8kg  
**Productivity:** 80/110 kg/h  
**Cable:** 10 mt with pliers  
**Power supply:** 12V electric  
**Motor:** with brushes

## OlivatorE-4800

Olive haverster for professional use. Thanks to the double speed regulated by a control unit, you can work quickly and with a higher harvest. The prongs-holder is fitted on a double bearing to ensure optimal movement stabilization. The harvester is very light: between 2.5 and 2.8 kg depending on the version.

**Lenght:** from 2100 to 3100mm  
**Weight:** 2,5kg  
**Productivity:** 90/120 kg/h  
**Cable:** 20 mt with connectors  
**Power supply:** 12V/48V electric  
**Motor:** replaceable brushes

**Lenght:** from 2400 to 3700mm  
**Weight:** 2,8kg  
**Productivity:** 90/120 kg/h  
**Cable:** 20 mt with connectors  
**Power supply:** 12V/48V electric  
**Motor:** replaceable brushes

### Extensible

To reach any height, Olivator can be extended up to 3.7 meters.

### New anti-vibration head

The harvesting head has been completely redesigned to ensure long-lasting duration, without effort or vibrations.

### Ergonomic handle

Robust in all its parts and comfortable to use. The position of the cable has been specially designed to avoid accidental breakage and always ensure natural movements.







## ACTIVE

Via Delmoncello, 12  
26037 - S. Giovanni in Croce (CR)

Phone: +39 0375 91742

Fax: +39 0375 91684

Email [Export@active-srl.com](mailto:Export@active-srl.com)

Copyright 2021 © - All Right Reserved

Images are for illustrative purpose only.  
We apologize for any typing and / or  
printing errors. They shall not be legally  
binding.